

MAHCERAM OUTDOOR










OUTDOOR FLOORING SYSTEM



Index

```
Texture

12 Brixton

13 Concrete Shapes

14 Rock

15 Garven

16 Pietra
```

Properties



| Water Absorption



Resistant To Stains



Resistant To Deep Abrasion



IUV Resistant



|Resistant To Salt



| Slip resistant



| Frost resistant



|Chemical resistant



| Easy To Clean



Resistant to Thermal Shocks



Resistant To Scratches



| Easy To Install

Versatile Solutions



Dry installation on grass

Effortless and rapid installation without the necessity of screeds, mortar, or adhesives, with a quick-drying feature.



Dry installation on gravel

Installation is both speedy and uncomplicated, thanks to the dry application method that requires no mortar, screeds, or adhesives, and dries quickly.




Installation with adhesive

Conventional adhesive-based lying method.




Dry installation on sand


The dry installation method is straightforward and swift, with no need for adhesives or complicated mortar and screed processes.



< Cement



Stone >





Brixton





Concrete Shapes





Rock






Garven





Pietra











Brixton

40*40 60*60 80*80 cm

□ 40*80 60*120 cm

[▽] 20 mm

Gray

Dark Gray







Concrete Shapes

☐ 40*40 60*60 80*80 cm ☐ 40*80 60*120 cm $\frac{\nabla}{\triangle}$ 20 mm

Light Gray

Gray

Dark Gray

Ivory







Rock

☐ 40*40 60*60 80*80 cm ☐ 40*80 60*120 cm $\frac{\nabla}{\triangle}$ 20 mm

Light Gray

Gray

Dark Gray

Ivory







Garven

40*40 60*60 80*80 cm

□ 40*80 60*120 cm

[▽] 20 mm


Light Gray


Gray

Dark Gray

Ivory







Pietra

40*40 60*60 80*80 cm


□ 40*80 60*120 cm

[▽] 20 mm

Gray

Dark Gray







Originality & Elegance